



TANDEM AXLE TRAILERS

- 4"X2" FRAME MAIN RAILS
- 4"X1-1/2" C-PURLIN
- 16" OC MAIN FRAME CROSS-MEMBERS
- 16" OC WALL CROSS-MEMBERS
- 24" OC ROOF CROSS-MEMBERS
- A-FRAME TRIPLE TONGUE
- 4 POSTIONS ADJUSTABLE COUPLER BRACKET
- ADJUSTABLE 2-5/16" BULLDOG WITH 12,500 LBS CAPACITY
- 2,000 LBS JACK WITH SAND FOOT
- TANDEM 3.5K DROP LEAF AXLES WITH EZ LUBE HUBS AND ELECTRIC BRAKES
- CUSTOM FABRICATION ON ALL HEADERS AND CORNER POSTS
- (4) 6K LBS D-RINGS W/BACKING PLATE WELDED TO FRAME ON ALL 7' WIDE TRAILERS
- POLYCOR COMPOSITE 0.080" THICK
- SEMI-SCREWLESS POLYCOR INSTALLATION
- SINGLE PIECE ALUMINUM ROOF
- TIRE/WHEEL - ST205/75R15 - 8 PLY
- TAIL SPOILER PACKAGE WITH LOADING LIGHTS W/OUTSIDE SWITCH
- 7-WAY CABLE CONNECTION
- LED LIGHTS: RUNNING, TAIL, LIC. PLATE & DOME W/SWITCH
- 3/4" PLYWOOD ON FLOOR AND RAMP
- 3/8" PLYWOOD ON WALLS
- 36" X 72" SIDE DOOR
- RV LATCH AND 45" BAR LOCK COMBO ON SIDE DOOR
- RAMP DOOR WITH SPRING ASSIST
- V-NOSE WITH 24" ATP
- NATM CERTIFIED STICKER
- SAFETY STICKERS

